

Application Instructions for Prolong

Prepare:

1. Wash the surface using a pH neutral shampoo to remove excess dirt or residue
2. Decontaminate the paint to remove any contaminants stuck to the surface

Correction:

Machine Polish the surface to remove any imperfections.

Degrease:

Remove polish residue using diluted Isopropyl Alcohol (IPA). Dilute the IPA in 30% water. For Example, in a 1L bottle add 300ml water and 700ml IPA.

Product Application

1. Gently mix the Ceramic Coating bottle and apply a minimum of 20 drops of product on the applicator pad and cover an area no bigger than 2x2ft. Work in cross-hatch pattern. Spread the product with your applicator pad and pass over twice horizontally and twice vertically.
2. Put the lid back on the bottle after applying on the applicator pad to stop the product from curing inside the bottle.

TIP: Apply the product generously on the applicator pad for even application. If there are streak marks on surface when applying add a few more drops on the pad and apply again.

3. The coating starts to bond to the surface immediately. Remove excess residue immediately using at least 2 microfiber cloths. We recommend using minimum 380gsm microfiber cloths to remove residue.
4. Use the first microfiber cloth to wipe off the bulk of residue
5. The second cloth will remove any remaining residue and haze marks. Avoid using too much force when wiping off as you may scratch the paint specially when working on softer paints.

Tip: If the applicator pad or microfiber cloth feels hard after a while then throw it away and use a new one otherwise, you will scratch the surface

6. Before moving onto the next panel, always inspect the area in good lighting and by checking in various angles so you haven't missed any residue.

TIP: If you have missed residue re-polish the affected panel and re-apply ceramic coating.

7. We recommend the vehicle should be stationery and surface must be kept dry post application for at least 12 hours.
8. After 12 hours the vehicle can be used but, we recommend avoiding manual wash for up to 7 days.

Application Video: <https://www.youtube.com/watch?v=efgxHLy2ZY8>

Layering

1. 3 layers of prolong must be applied for 5-year warranty
2. Wait 45 minutes between layers in summer and 60 minutes in winter
3. To enhance the performance of the coating, 1 layer of enhance can be applied every 12 months